



28.09.2004



INVESTOR IN PEOPLE

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 09 NOV 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 13 September 2004

BEST AVAILABLE COPY

Patents Form 1/77

Patents Act 1977
(Rule 16)The
Patent
Office29SEP03 EB40695-2 000393
P01/7700 0.00-0322738.6**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

2003P11505/GB/P68/NC/st

2. Patent application number
(The Patent Office will fill in this part)

0322738.6

29 SEP 2003

3. Full name, address and postcode of the or of
each applicant (underline all surnames)

Siemens Aktiengesellschaft

Wittelsbacherplatz 2
D-80333 Munich
Germany

Patents ADP number (if you know it)

720623010

If the applicant is a corporate body, give the
country/state of its incorporation

DE

4. Title of the invention

Network Entity

5. Name of your agent (if you have one)

Neil Condon

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)Siemens Shared Services
Intellectual Property Department
Siemens House, Oldbury
Bracknell, Berkshire RG12 8FZ
United Kingdom

Patents ADP number (if you know it)

7761000002

6. If you are declaring priority from one or more
earlier patent applications, give the country
and the date of filing of the or of each of these
earlier applications and (if you know it) the or
each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)7. If this application is divided or otherwise
derived from an earlier UK application,
give the number and the filing date of
the earlier application

Number of earlier application

Date of filing
(day / month / year)8. Is a statement of inventorship and of right
to grant of a patent required in support of
this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

0081217 29-Sep-03 02:24

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

Continuation sheets of this form

Description	13	—
Claim(s)	2	—
Abstract	1	—
Drawing(s)	2	—

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 5/77) 1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

Fee Sheet

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 29/09/2003

Neil Condon

12. Name and daytime telephone number of person to contact in the United Kingdom

Neil Condon

Neil Condon

01344 85 0066

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Network Entity

Technical Field

5 This invention relates to a network entity. In particular, but not exclusively, the invention relates to a Session Initiation Protocol (SIP) network entity.

Background

10

The session initiation protocol (SIP), which is described in RFC 3261, is a signalling protocol for setting up, managing and tearing down of voice, video and other multi-media sessions in packet based networks. SIP
15 is designed simply to handle these aspects of communication, other protocols such as Real Time Protocol (RTP) are used for actual data transport. SIP is an application layer protocol that can run over other protocols such as User Datagram Protocol (UDP) and
20 Transmission Control Protocol (TCP).

A SIP network is typically composed of four types of logical SIP entities, namely, User Agents (UA), Proxy Servers, Redirect Servers and Registrars.

User Agents (UA) are endpoint entities that initiate
25 and terminate SIP sessions by exchanging requests and responses. A UA contains a User Agent Client (UAC) and a

User Agent Server (UAS). A UAC is a client application that initiates SIP requests. A UAS is a server application that contacts a user when a SIP request is received and that returns a response on behalf of the user. Typical devices that have a UA function in a SIP network include PCs, IP telephones and automated answering services.

A proxy server is an intermediary entity that acts as both a server and a client for making requests on behalf of other clients. Requests are serviced either

~~internally or by passing them on to other servers.~~ A proxy server may receive requests and forwards them to another server (called a next-hop server), which has more precise location information about the callee. The next-hop server might be another proxy server, a UAS, or a redirect server.

A redirect server is a server that accepts a SIP request, maps the SIP address of the called party into a new address and returns it to its client, typically a proxy server. Registration servers are continually kept updated on the current locations of users.

The primary function of proxy and redirect servers is call routing, the determination of the set of servers to traverse in order to complete the call. A proxy or redirect server can use any means at its disposal to

determine the 'next-hop' server, including executing programs and consulting databases.

The SIP protocol is a text-based protocol partly
5 modelled on HTTP. There are two types of SIP messages,
namely, requests, which are sent from clients to servers
and response, which are sent from servers to clients. A
request and the responses that follow it are known as a
SIP transaction.

10 Request methods defined in the protocol include:
'INVITE' which is used to initiate a session or change
session parameters, 'ACK' which is used to confirm that a
session has been initiated and 'BYE' which is used to
terminate a session.

15 Response messages contain numeric response codes and
there are two types of responses and six classes.
'Provisional (1xx class)' responses are used by a server
to indicate progress of SIP transactions. An example of
a provisional response is the response code 180 'Ringing'
20 response. 'Final (2xx, 3xx, 4xx, 5xx, 6xx
classes)' responses are used to terminate SIP
transactions. An example of a final response is the
response code 200 'OK' response.

A caller establishes a call by issuing an 'INVITE'
25 request. This request contains header fields used to
convey information about the call. The most important

header fields are 'To' and 'From', which contain the callee's and caller's SIP address, respectively. The Subject header field identifies the subject of the call.

If the callee accepts the call, it responds with an 'OK' response. Connection is done using a three way handshake and so the caller responds with an 'ACK' message to confirm receipt of the 'OK' response.

SIP provides for a variety of multi - media communication features similar to those provided by traditional Private Branch Exchanges, for example, call waiting, call hold, Music on Hold, and conference calling. It is envisaged that many new such features for client endpoint-to-endpoint communication in SIP networks will be developed. Communication will sometimes occur in circumstances where one of the endpoints provides a new feature that the other endpoint does not. To date, if there is a difference in the set of features available at one endpoint in a SIP network and the set of features available at the other endpoint in the network, the endpoints communicate using their lowest common feature set.

The present invention aims to solve the problem of connecting an endpoint having an enhanced communication feature set and an endpoint having a basic communication feature set in a manner that allows the enhanced feature set to be used.

According to the invention there is provided a network entity for operating in a communications channel between a first end point and a second end point in a packet based communications network, the first end point having available a first set of communication features and the second end point having available a second set of communication features, including at least one communication feature unavailable to the first end point, the network entity comprising means for acting as a client application for the first end point and as a server application for the second end point and arranged to exchange signalling information with the end points to enable the second end point to utilise the at least one communication feature during communications with the first end point.

An embodiment of the invention will now be described with reference to the accompanying drawings in which:

Figure 1 illustrates a system embodying the invention;

Figure 2 illustrates a message sequence chart

25

Figure 1 illustrates schematically a system embodying the present invention. The system comprises a

28/08 03 14:24 FAX TTS 2033 220011
first SIP user agent 1, a second SIP user agent 2, and a SIP basic call enhancer 3.

The first SIP user agent 1 and the second SIP agent 2 may both for example be IP telephones. In this embodiment, the first SIP user agent 1 provides only a basic SIP functionality while SIP user agent 2 provides a more advanced SIP functionality. By basic SIP functionality, it is meant that the first SIP user agent 1 supports only session initiation and termination but does not support session modification. The second SIP user agent 2 does support session modification and provides an enhanced set of telephony features, including for example, call transfer, conference, call hold, Music on Hold (MOH), which are not provided by the first SIP user agent 1.

The SIP basic call enhancer (BCE) 3, is an object located within the communication channel between the first 1 and second 2 SIP user agents. The functionality of the BCE may be provided by a suitably configured Server device located in the SIP network between the first 1 and second 2 SIP user agents.

In operation, during communication between the first 1 and second 2 SIP user agents, the BCE 3 communicates concurrently with both user agents by acting as a SIP server for the first SIP user agent 1 and as a SIP client for the second SIP user agent 2. In doing so, the BCE 3

processes and manages a flow of SIP messages that enable the first 1 and second SIP user agents 2 to utilise the extra telephony features supported by the second SIP user agent 2 and which normally could not be used in a session 5 between the two user agents.

The BCE 3 comprises a user agent server part 4 for exchanging messages with the first SIP user agent 1 and a user agent client part 5 for exchanging messages with the second SIP user agent 2. These components are standard 10 SIP components as defined in RFC 3261.

The BCE 3 further comprises a local configuration store 5 for storing information required for the BCE to be able to route messages. This information comprises SIP URI address, e.g. the TCP/IP addresses and port 15 numbers and the Media-Stream address e.g. UDP address and port numbers.

A call router 6 provides the intelligence needed to involve the first 1 and second 2 user agents in enhanced SIP sessions.

20 The call router 6 receives session request messages from the user agent server part 4 and in response generates an appropriate session request message for the user agent client part 6.

The call router 6 uses information contained in the 25 store 5 to substitute SIP URI and Media Stream addresses in the request messages received from the user agent

client part 6 with appropriate new addresses in the messages passed to the user agent client part 6 for transmission onwards in the network.

Furthermore, the call router 6 generates its own request messages for the second user agent 2 side of the network and interprets event messages received from this side of the network.

All messages sent from the user agent server part 4 to the call router 6 and from the call router 6 to the user agent part 5 pass via a session controller 7. The session controller 7 thus interacts with the call router 6 on one side and with the user agent server part and the user agent client part on the other side, to keep track of session states and progress. Therefore the session controller 7 behaves like a state machine automat, acting on the user agent session states and routing messages.

A payload router 8 is needed because the SIP protocol specifies the endpoints for a media stream. The first user agent 1 can only handle a single media stream session to the BCE 3 and cannot change media stream capabilities within a session. In other words, the first user agent 1, as a basic SIP client, cannot handle multiple media streams within a SIP session. The second user agent 2 can handle multiple media streams within a SIP session (i.e. Re-invite) because this user agent supports an enhanced feature set. The main task of the

payload router 8 is to manage any media streams in such away that the BCE 3 acts as a virtual end point to both the first 1 and second 2 user agents in respect of these media streams.

5 Referring now to Figure 2 of the accompanying drawings there is illustrated a message sequence chart.

In the sequence illustrated in Figure 2, the first user agent 1, the agent having the basic SIP functionality, calls the second user agent 2, the agent
10 having the enhanced SIP functionality. The second user agent 2 is busy on another call and is initially unable to accept the first agent's call. One telephony feature available to the second user agent 2 but not to the first user agent 1 is the well known Music on Hold (MOH)
15 feature.

The BCE 3 co-ordinates with the SIP network the connection of the first user agent 1 to a MOH entity and the subsequent connection of the first 1 and second 2 agents when the second agent is ready to receive the
20 first agents call 1.

Referring now to Figure 2 in more detail, at step 100, the first user agent 1 transmits an INVITE message to the second user agent 2. In accordance with standard SIP procedure, the Invite message is routed through a
25 sequence of 'next hop' proxy servers (not shown) each server in the sequence having more precise information on

the location of the second user agent 2 than the server before it. The final server in this sequence (not shown) is configured to redirect incoming Invite messages for the second user agent 2 to the BCE 3. The Invite message
5 thus arrives at the Server Part of the BCE 3. The redirection of the message may be indicated to the first user agent 1 by the SIP network using standard SIP mechanisms.

The user agent server part of the BCE 3 receives the
10 Invite message and forwards it to the session controller
~~7. The session controller 7 handles the session state~~
(e.g. state = initiated).

The Invite message is passed to the call router 6 which fits URI address information in the SIP message
15 header and the Media-Stream addresses in the SDP protocol parameters within the standard SIP message body.

The message is passed to the user agent client part of the BCE 3 which transmits the message onwards in the network, step 101, to a SIP proxy/redirect server 9.

20 The SIP proxy server 9 is aware that the second user agent 2 is busy and so redirects the message, step 102, to a Music on Hold (MOH) feature 10. The server 9 may be kept aware of the session status of the second user agent 2 by a SIP presence service. Alternatively, the server 9
25 may be a so called stateful proxy server that is able to

derive the session status of the second user agent 2, by virtue of the protocol flow between the two.

The MOH feature 10 is a SIP invocable feature that provides call announcements and music to a caller that has been placed on hold.

The MOH 10 responds to the server 9 by transmitting a Ringing reply, step 103, which the server 9 in turns routes to the client part of the BCE 3, step 104 and which is routed from the server part of the BCE 3 to the first user agent 1, step 105.

Likewise, an OK message is transmitted from the MOH 10 to the sever 9, step 106, which the server 9 in turns routes to the client part of the BCE 3, step 107 and which is routed from the server part of the BCE 3 to the first user agent 1, step 108.

The first user agent 1 responds by transmitting an Ack message which is received at the server part of the BCE 3, step 109, and in turn, an ACK message is routed from the client part of the BCE 3 to the server 9, step 110, and from the server 9 to the MOH 10, step 111.

This exchange of messages sets up a Real Time Protocol (RTP) media flow between the MOH 10 and the payload router 8 of the BCE 3, and another RTP media flow between the payload router 8 and the first user agent 1. This enables hold announcements and music to be delivered from the MOH 8 to the first user agent 1.

When the existing session of the second user agent 2 ends, the server 9 is informed and in turn, informs the BCE 3 by transmitting an Invite (HOLD) message, step 112, to initiate a termination of the MOH session. The BCE 3 responds with an OK message, step 113, prompting an ACK message from the server 9, step 114.

To terminate the RTP connection between the BCE 3 and the MOH 10, the server 9 sends a BYE message to the MOH 10, step 115, which responds with an OK message, step 116.

~~At this point, the SIP connection between the BCE 3~~
and the MOH 10 is terminated and thus the first user agent 1 no longer receives a MOH media stream, but the SIP connection between the first user agent 1 and the BCE 15 remains in place.

The server 9 now establishes a connection between the second user agent 2 and the BCE 3. To this end, the server 9 sends an Invite message to the second user agent 2, step 117, prompting an exchange of a Ringing, an 'OK' and an ACK message between the two (for brevity all these messages are illustrated as a single step 117).

Furthermore, the server 9 sends an Invite (Re-invite) message to the BCE, step 118, which replies with an OK message, step 119, prompting an ACK message from the server 9, step 120.

At this point, if the second user agent 2 goes off hook, the BCE's 3 payload router connects the RTP channels between the first user agent 1 and the second user agent 2 allowing them to communicate.

5 In this scenario, the first user agent 1 initiates termination of the session by transmitting a BYE message to the BCE 3, step 121, which responds with an OK message, step 122. This terminates the SIP session between the BCE 3 and the first user agent 1.

10 The BCE 3 transmits a BYE message via the server 9, step 123, to the second user agent 2, step 124. The second user agent 2 responds with an OK message transmitted via the server 9, step 125, to the BCE step 126. This terminates the SIP session between the BCE 3
15 and the second user agent 2.

Having thus described the present invention by reference to a preferred embodiment, it is to be well understood that the embodiment in question is exemplary only and that modifications and variations such as will
20 occur to those possessed of appropriate knowledge and skills may be made without departure from the scope of the invention as set forth in the appended claims.

CLAIMS

1. A network entity for operating in a communications channel between a first end point and a second end point
5 in a packet based communications network, the first end point having available a first set of communication features and the second end point having available a second set of communication features, including at least one communication feature unavailable to the first end
10 point, the network entity comprising means for acting as a client application for the first end point and as a server application for the second end point and arranged to exchange signalling information with the end points to enable the second end point to utilise the at least one
15 communication feature during communications with the first end point.

2. A network entity according to claim 1 comprising call routing means for addressing signalling information
20 that is exchanged between the entity and the end points or the entity and the network.

3. A network entity according to claim 2 comprising payload routing means for addressing payload data
25 received at the entity for routing to one or other of the end points.

4. A network entity according to any preceding claim wherein the entity is a Session Initiation Protocol Entity.

ABSTRACT

5 There is described a Session initiation Protocol (SIP)
network entity for operating in a communications channel
between a first SIP end point and a second SIP end point
in a communications network. The first SIP end point has
available a first set of communication features and the
10 second SIP end point has available a second set of
communication features, including at least one
communication feature, for example Music on Hold, that is
unavailable to the first SIP end point. The network
entity comprises means for acting as a client application
15 for the first SIP end point and as a server application
for the second SIP end point and is arranged to exchange
signalling information with the SIP end points to enable
the second SIP end point to utilise the at least one
communication feature during communications with the
20 first SIP end point.




FIGURE 1




Figure 2

ACB CT/EP2004/010021 AKE



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.